

Console with the LPAR tool

by PowerCampus⁰¹

Contents

- ▶ LPAR-Tool
- ▶ Opening a console „*lpar console*“
- ▶ Closing a console „*lpar rmconsole*“
- ▶ View console sessions
- ▶ Further commands which can open a console

LPAR tool

- ▶ Command line tool for the administration of LPARs
- ▶ easy, fast and efficient in use
- ▶ Administration of any number of HMCs, managed systems and LPARs
- ▶ can be integrated into your own scripts or automation tools

Opening a console session

- ▶ With the LPAR tool a console can be opened at any time:
- ▶ `$ lpar console lpar01`

Open in progress

Open completed.

PowerPC Firmware

SMS 1.7 (c) Copyright IBM Corp. 2000,2008 All rights reserved.

- - - - -

Main Menu

1. Select Language
2. Setup Remote IPL (Initial Program Load)
3. Change SCSI Settings
4. Select Console
5. Select Boot Options

...

Closing a console session

- ▶ The escape sequence „~.“ can be used to close an open console session:

- ▶ ...

- ▶ ~.

- ▶ Terminate session? [y/n] y
- ▶ Shared connection to hmc01 closed.
- ▶ \$

Console session is already open

- ▶ If a console to the LPAR is already open, the following message is shown:

- ▶ `$ lpar console lpar01`

```
A terminal session is already open for this partition.  
Only one open session is allowed for a partition.  
Exiting..  
Received end of file, Exiting.  
Shared connection to hmc01 closed.  
$
```

- ▶ By using the option „-f“ (force), the open session will be closed.

Console session hangs

- ▶ A hanging console session can be terminated using the command „*lpar rmconsole*“:
- ▶

```
$ lpar rmconsole lpar01  
/bin/stty: standard input: Inappropriate ioctl for device  
$
```
- ▶ The following message appears in the open console session that is being closed:
...

```
Connection has closed
```



```
This session is no longer connected. Please close this  
window.
```


View console sessions

- ▶ Open console sessions can be viewed indirectly through the connected HMCs. The command „*hmc lslogon*“ can be used in this case:

```
▶ $ hmc lslogon hmc01
▶ USER_NAME  TTY_ID  LOGON_TIME          ACCESS_LOCATION
▶ TASK_NAME  TTY_ID  START_TIME              USER_NAME  PID
user01      pts/1    2022-10-10 09:38      172.10.10.15
mkvterm     pts/1    Oct 10 09:38:18 2022    root      24583
$
```

- ▶ A console session can be recognized by the task name „*mkvterm*“.

Further commands that can open a console

- ▶ There are a number of other commands that can be used to open a console:
- ▶ When activating an LPAR with „*lpar activate -c*“.
- ▶ When shutting down an LPAR with „*lpar shutdown -c*“.
- ▶ When shutting down the operating system of an LPAR with „*lpar osshutdown -c*“.
- ▶ When initiating a dump of an LPAR with „*lpar dumprestart -c*“.
- ▶ In all cases, a console session can be started with the „*-c*“ (console) option.

Questions about the LPAR-Tool and PowerCampus 01

- ▶ ...
- ▶ Questions about the LPAR tool at any time:
info@powercampus.de
- ▶ Problems can be reported to: support@powercampus.de

Thank you for letting us introduce the
LPAR tool!

PowerCampus⁰¹